



**RAKtherm Stabi Composite Pipe RR-R PN 20 With Aluminium Thickness 0.2 mm
According To DIN 8077/78**

Art.-No.	Dimension	Packing Unit	Outer Diameter (OD)mm	Wall Thickness (S)	Internal Diameter (ID)mm	Water content l/mt	Kg / mt
PS20-20	20 mm	100 mts	20	2.8	14.4	0.163	0.220
PS20-25	25 mm	100 mts	25	3.5	18	0.254	0.315
PS20-32	32 mm	40 mts	32	4.4	23.2	0.415	0.470
PS20-40	40 mm	40 mts	40	5.5	29	0.651	0.720
PS20-50	50 mm	20 mts	50	6.9	36.2	1.029	1.060
PS20-63	63 mm	20 mts	63	8.6	45.8	1.633	1.650
PS20-75	75 mm	20 mts	75	10.3	54.4	2.307	2.280
PS20-90	90 mm	12 mts	90	12.3	65.4	3.318	3.200
PS20-110	110 mm	8 mts	110	15.1	79.8	5.674	4.670

**RAKtherm Stabi Composite Pipe RR-R PN 25 With Aluminium Thickness 0.2 mm
According To DIN 8077/78**

Art.-No.	Dimension	Packing Unit	Outer Diameter (OD)mm	Wall Thickness (S)	Internal Diameter (ID)mm	Water content l/mt	Kg / mt
PS25-20	20 mm	100 mts	20	3.4	13.2	0.137	0.244
PS25-25	25 mm	100 mts	25	4.2	16.6	0.216	0.350
PS25-32	32 mm	40 mts	32	5.4	21.2	0.353	0.534
PS25-40	40 mm	40 mts	40	6.7	26.6	0.556	0.816
PS25-50	50 mm	20 mts	50	8.3	33.4	0.866	1.204
PS25-63	63 mm	20 mts	63	10.5	42	1.385	1.860
PS25-75	75 mm	20 mts	75	12.5	50	1.963	2.586
PS25-90	90 mm	12 mts	90	15	60	2.827	3.656
PS25-110	110 mm	8 mts	110	18.3	73.4	4.208	5.372