

RAKtherm Stabi Composite Pipe RR-R PN 25 With Aluminium Thickness 0.2 mm
According To DIN 8077/78 Special technology with black layer (UV resistant)
for out door and external installations under sunlight

| Art.-No. | Dimension | Packing Unit | Outer Diameter (OD)mm | Wall Thickness (S) | Internal Diameter (ID)mm | Water content l/mt | Kg / mt |
|------------|-----------|--------------|-----------------------|--------------------|--------------------------|--------------------|---------|
| PSUV25-20 | 20 mm | 100 mts | 20 | 3.4 | 13.2 | 0.137 | 0.241 |
| PSUV25-25 | 25 mm | 100 mts | 25 | 4.2 | 16.6 | 0.216 | 0.350 |
| PSUV25-32 | 32 mm | 40 mts | 32 | 5.4 | 21.2 | 0.353 | 0.542 |
| PSUV25-40 | 40 mm | 40 mts | 40 | 6.7 | 26.6 | 0.556 | 0.805 |
| PSUV25-50 | 50 mm | 20 mts | 50 | 8.3 | 33.4 | 0.866 | 1.217 |
| PSUV25-63 | 63 mm | 20 mts | 63 | 10.5 | 42 | 1.385 | 1.860 |
| PSUV25-75 | 75 mm | 20 mts | 75 | 12.5 | 50 | 1.963 | 2.586 |
| PSUV25-90 | 90 mm | 12 mts | 90 | 15 | 60 | 2.827 | 3.656 |
| PSUV25-110 | 110 mm | 8 mts | 110 | 18.3 | 73.4 | 4.208 | 5.372 |